**A4 Mono Printer and MFP** 



## RICOH P 311 M 320F



### **Stability and Performance**

Ensure uninterrupted workflow with print-on-demand from anywhere functionality

# Easy to change, long-lasting print cartridges

RICOH P 311 and M 320F offer an All-in-One print cartridge with a long-lasting 7,000 print yield. When you do need to replace the cartridge, there's no disruption to your workflow. Simply slot in the new one via the convenient full front-access design.





\*Image shown is with optional tray

#### Easy document sharing digitally

The feature-rich RICOH M 320F multi-function printer is made for easy sharing of all your important information. The 35-sheet Automatic Reversing Document Feeder (ARDF) allows you to scan and send a full-colour presentation to colleagues for review instantly via multiple Scan-to capabilities, including Scan-to-Email, FTP, Folder, USB drive and more.

#### Work from anywhere

Access and share all your documents even when not in the office via the RICOH Smart Device Connector app on your mobile device. Mopria® or AirPrint® lets you send print jobs directly to your RICOH printer from your mobile phone. Once you're back in the office, simply pair your Android® device via the Near Field Communications (NFC) tag on the printer to authenticate and transfer information and print.





#### Security is in our DNA

Recognising your need to keep your data secure, we've added robust security layers. Protect confidential documents from unauthorised viewing with the Locked Print function. Network encryption also ensures data transmission remains secure.

#### RICOH P 311 / M 320F

MODEL		RICOH P 311	RICOH M 320F
GENERAL			
Configuration		Desktop	
Technology		Laser (Mono)	
Function(s)		Print	Print, Copy, Scan, Fax
Display panel		4-Line operation LCD	4.3" colour touch panel
Processor		350 MHz	400 MHz
Memory		128 MB	256 MB
Mobile capability		RICOH Smart Device Connector, Apple AirPrint®, Mopria®	
Printer language		PCL5e, PCL6, PostScript 3 emulation TCP/IP	
Network protocol			
Interface Operating system	Standard Optional	10Base-T/100Base-Tx (Ethernet), USB 2.0 Type A x 1— rear, USB 2.0 Type B— rear, NFC tag IEEE 802.11a/b/q/n/ac (Wire	10Base-T/100Base-Tx (Ethernet) USB 2.0 Type A x 2—1 x rear & 1x front, USB 2.0 Type B x 1— rear, NFC tag
	Windows®	Windows® 8.1, Windows® 10, Windows® Server 2012, Windows®	<u> </u>
	Mac	Mac OS v10.10 - v11	
	Other	Linux	
PRINTER			
Duplex printing		Auto	
Print speed (A4)		32 ppm (Simplex), 13 ppm (Duplex)	
First print out time		7.1 sec	onds
Warm up time		26 seconds or less	30 seconds or less
Print resolution		600 x 600 dpi (Default), Windows®: 600 x 600 dpi, 1,200 x 600 dpi, 1,200 x 1,200 dpi MAC: 600 x 600 dpi Linux: 600 x 600 dpi, 1,200 x 1,200 dpi	
Average print volume		700 - 5,800 pages	
Duty cycle		35,000 pages/month	
COPIER			
Copy speed (A4)		-	Up to 32 ppm
Document feeder type		-	Automatic Reversing Document Feeder
Document feeder capacity		-	35 sheets
Resolution		-	300 x 600 dpi (ARDF), 600 x 600 dpi (Platen)
Multiple copy		-	Up to 99
Copy features			Zoom Range: 25%-400%, Image density: 5 levels, Image quality: Text, Photo, Mixed
			Combined Copy, Memory Copy, ID Card Copy, Series Copy
SCANNER (AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Scan speed (A4 ARDF)		<u> </u>	Mono: 13 impressions/minute, Colour: 4.5 impressions/minute
Resolution Original size		<u>-</u>	300 x 600 dpi (ARDF), 19,200 x 19,200 dpi (Platen, PC TWAIN)  A4
Bundled drivers		<u> </u>	Network TWAIN, WIA
Scan to			Scan to email, Scan to folder, Scan to FTP, Scan to USB, TWAIN scanning
FACSIMILE			Scan to chian, scan to rolder, scan to 111, scan to 035, 144AiN scanning
Circuit			PSTN, PABX
Compatibility		-	T.30 (ITU-T SuperG3)
			Horizontal: 200 dpi-8dots/mm,
Resolution		•	Vertical 100 dpi-3.85dots/mm, 200 dpi-7.7dots/mm
Transmission speed		-	33.6 Kbps—2,400 bps with automatic shift down
Compression method		<u>•</u>	MH, MR, MMR
Reception features		-	Automatic, Paperless fax, Manual, Main scan auto reduction
Other supported features		-	Quick dial—8 (20 digits for name, 40 digits for numbers), Speed dial—100 (20 digits name, 40 digits for numbers), Label registration for Quick/Speed, Redial—automatic manual, Redial interval time—2 selections (5 minutes: default, 6 minutes), Only redials to minute in the control of the cont
SECURITY Authentication		Locked Print	
Authentication PAPER HANDLING		Locked	
Recommended paper size		A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican Oficio, Indian Legal, Envelopes, Australian Foolscap	
Paper input capacity  Standard		250 sheets (Bypass: 50 sheets), Maximum: 300 sheets	
With optional paper tray		Paper Bank PB1130: 250 sheets, Maximum 550 sheets	
Paper output capacity Paper weight		125 sheets 50 sheets 52 to 162 <i>g/m</i> <sup>2</sup>	
		52 to 16	۷ yııı
Dimensions (W x D x H)		370 mm x 392 mm x 262 mm	405 mm x 392 mm x 420 mm
Weight  Power consumption (Max)		Less than 13.0 kg 1,02	Less than 18.0 kg
Power consumption (Max) Ready mode		63.8 W	65.7 W
Energy saver (Sleep)		0.72 W	03.7 W
Power source			
CONSUMABLES		220–240 V, 50/60 Hz, 4.3 Amps	
AIO toner cartridges (K) (Extra high yield)		Black: Approx. 7,000 pages	
	asuring method ISO/IEC 1975.		··· p-gov
Shipped with Starter 1	Toner that yield approximate	ly (Black: Approx. 7,000 pages)	
OPTIONS			
Interface		IEEE 802.11a/b/g/n/ac (Wireless LAN) and Wi-Fi Direct	
Optional paper tray		Paper Bank PB1	130: 250 sheets



13 RICOH ricoh.com.au

Ricoh Australia Pty Ltd, 2 Richardson Place, North Ryde, NSW 2113, Australia, 13 Ricoh (13 74 264)

Ricch\* and the Ricch Logo are registered trademarks of Ricch Company, Ltd. All other trademarks are the property of their respective owners.

©2022 Ricch Australia Py Ltd. All Rights Reserved. The content of this document, and the appearance, features and specifications of Ricch products are subject to change from time to time without notice.

Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricch makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricch products and services are as set forth in the express warranty statements accompanying them.







